

MADE IN THE USA



**Durable
Screen
Protection**



SPECIFICATIONS

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Weld Range	Pins → up to 10GA Studs → up to #10
Duty Cycle	15-30 pins per minute
Weight	11.5 lbs.
Dimensions (LxWxH)	12.5" x 9.8" x 8.0"
Primary Power	Universal Input: 85-250VAC @ 50/60Hz Fusing Requirement: 7A
Charge Voltage	35-100VDC

SYSTEM FEATURES

- Less than 1 second recharge time for pin welding
- Intuitive touchscreen interface with preset values for fast, accurate, and repeatable weld settings
- Set-Point discharge: Unit discharges directly to a new setpoint without discharging completely
- Universal input voltage: No need to re-tap the machine for 110 or 220 input voltages
- Low input voltage capability enables operation with long extension cords
- Contact and trigger indicators for fast troubleshooting of hand tool and weld cable maintenance issues
- Thermal and voltage protection indicators to protect the unit from damage due to overheating or poor input power
- Mounted in a rugged outer case for greater durability and appearance
- Hand tool has an adjustable spring to apply the correct spring pressure for every welding application
- Hand tool can be configured for "B" collets, "CI" collets, "Euro" collets, and standard tapered chucks

Complete System Includes:

(1) AGM Insul-Pro Power Supply, (1) Ground Cable Assembly, (1) CD Stud Gun, (1) Phenolic CD Foot, (2) 7" Legs, and (1) Collet Adapter